

**duravent**<sup>™</sup>  
GROUP

**RUTLAND**  
TRUSTED SINCE 1883

# HOME & HEARTH

RETAIL PRODUCT CATALOG



140+ YEARS OF INNOVATION



*We offer a wide range of quality products to maintain, clean, and repair wood or gas stoves, fireplaces, hearths, and chimneys both indoors and outdoors, backed by 140+ years of expertise and innovation. Check out our new grill, household, and outdoor cleaning products!*

## CONTENTS

### NEW PRODUCTS

CREOSOTE & SOOT REMOVERS	5
FANS	5
FIRE STARTERS	6
RAINBOW FLAME® CRYSTALS	6
GASKETS & INSULATION	7
CEMENTS & MORTARS	8
COMING SOON	8
FIREBRICKS	9
CLEANERS	10
MISCELLANEOUS	11

### FIREPLACE & HEARTH

FIRE STARTERS	13
RAINBOW FLAME® CRYSTALS	13
CREOSOTE & SOOT REMOVERS	14-16
ACCESSORIES & GLOVES	17

### MAINTENANCE

CLEANERS	18-19
CEMENTS & MORTARS	20-23
FIREBRICKS	23
GASKETS & INSULATION	24-25
HOME & CHIMNEY CARE, PAINTS	27
POLISHES	28
SEALANTS & ADHESIVES	29

### BRUSHES & RODS

BRUSHES	31
RODS & ADAPTERS	32

INDEX	34
-------	----

 **LOOK FOR THIS SYMBOL FOR  
DVG-STOCKED PRODUCTS**

## NEW ICONS

Look for these icons to easily identify Rutland's signature **DIY** categories & products, **CLEAN BY RUTLAND**, and our new **FINER FIRE COLLECTION™**.





***NEW  
PRODUCTS***



## CREOSOTE & SOOT REMOVERS

### PELLET STOVE CREOSOTE REMOVER

Helps prevent dangerous creosote buildup in pellet stoves, wood stoves, and fireplaces. Concentrated creosote removing formula combined with high quality wood pellets dried to 2-5% moisture content.

Recommended usage 2x/week

- ☀️ **98P 8 oz Box (12 per case)**
- ☀️ **98P03 3 lb Bag (5 per case)**
- ☀️ **98P05 5 lb Bag (4 per case)**



USE: Pellet Stove, Fireplace, Wood Stove

### CREOSOTE ANTIDOTE

Helps prevent dangerous creosote buildup in wood stoves and fireplaces. Made with 100% recycled hardwood and powered by creosote concentrate technology.

- ☀️ **98A 6 lb Box (2 per box)**



USE: Fireplace, Wood Stove

### CREOSOTE CONCENTRATE TOSS-IN PACKETS

Rutland's Powerful creosote remover in convenient toss in packets. Made with Craft Paper. Concentrate formula 3x.

- ☀️ **97C5 5 Pack Box (60 per case)**
- ☀️ **97C20 20 Pack Display (8 per case)**



USE: Pellet Stove, Fireplace, Wood Stove

### CREOSOTE CONCENTRATE

Rutland's Powerful creosote remover in a convenient and economical tub. Two scoops per treatment.

- 19701 1 lb (12 per case)**
- 19702 2 lb (6 per case)**



USE: Fireplace, Wood Stove

**WARNING:** These products can expose you to harmful chemicals. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## FANS

### OSCILLATING HEAT-POWERED WOOD STOVE FAN

5-blade, 60° oscillating, heat-powered wood stove fan generates its own electricity from the heat of the stove. The fan starts automatically. The hotter the stove, the faster the fan blades rotate resulting in more air circulated. Rutland's fans increase stove efficiency, decrease fuel usage, and warm rooms faster all with near silent operation. Designed for freestanding stoves with normal surface temperatures ranging between 122 – 650° F. Needs no Electricity, Cords or Batteries. This powerful fan provides an industry leading 220 CFM!

- ☀️ **FN05 1 per case**

USE: Wood Stove



## FIRE STARTERS

### **ONE MATCH® FIRE STARTER GEL - PATRIOT PACK**

A clean burning, odor-free gelled fire starter for hard-working Americans. Safe for cooking over & won't flavor food when used for cooking All-American meals. The best fire starter for pellet stove owners - mix gel with pellets and ignite! Thicker than the rest, with this Top-Secret American formula, these colors don't run!

**49USA (6 per case)**

USE: Fireplaces, Wood Stoves, Pellet Stoves, Fire Pits, Chimeneas, Ceramic Grills



### **SAFELITE 2X JUMBO FIRE STARTERS**

Rutlands Jumbo Firestarters are the best to start a fire in the toughest conditions. 20 minute burn time. No flare ups.

**50J (9 per case)**

USE: Fireplaces, Wood Stoves, Pellet Stoves, Fire Pits, Chimeneas, Ceramic Grills



### **BBQ FIRE STARTERS**

Made with vegetable wax. Light weight and portable. Burns up to 10 minutes. 100% natural materials.

**50W (9 per case)**

USE: Fireplaces, Wood Stoves, Pellet Stoves, Fire Pits, Chimeneas, Ceramic Grills



## RAINBOW FLAME® CRYSTALS

### **RAINBOW FLAME® CRYSTALS**

Add beautiful and long-lasting blue, green, and purple flames to your wood burning fire with convenient packets. Light weight and portable. Great for making backyard memories.

-  **715P Craft Paper Toss-in Packets (25 per case)**
- 71599 XL 2.5 lb cannister (6 per case)**

USE: Fireplace, Fire Pit, Wood Stove, Outdoor, Indoor





## GASKETS & INSULATION

### PREMIUM SELF-ADHESIVE CERAMIC GRILL REPLACEMENT GASKET

Ceramic Grill and Smoker gasket replacement. Fits sizes XXL, XL, Large, Medium, Small and Mini. Premium gasket intended for Big Green Egg and similarly sized grills. Designed to comfortably endure 5+ clean burns at 700°F. High heat-resistant self-adhesive strip featuring 3M technology. White Fiberglass, longer lasting and more durable than Nomex and felt gasketing. Bonus gasketing included for replacing the chimney seal.

- 99N12 12' (15 per case)
- 99N12G 12' (15 per case)
- 99N17 17' (15 per case)
- 99N17G 17' (15 per case)



 Scan to view installation instructions.







# PIZZA OVEN

Building a pizza oven is rewarding project, and a great way to enjoy homemade pizzas with that authentic wood-fired flavor. Our line of DIY Pizza oven SKU's and Rutland's Perfect Pizza & BBQ Gourmet Hickory Hunks™ will deliver perfect pizza & BBQ every time!



## CEMENTS & MORTARS

### DRY MIX 211®

**New convenient size!** Power of Dry mix in a convenient 2.5 pound tub. Refractory mortar that is ideal for joining or repairing masonry flue tile in any gas or wood fireplace and wood, coal, or pellet stove chimney. Dry mix cement, just add water and trowel into place. Can be used as a parge coating (thin over-coat) when building or repairing fireboxes. Perfect for up to six RUTLAND firebox bricks! Dark grey finish.



**21125 2.5 lb tub (6 per case)**

USE: Fireplace, Wood Stove, Pellet Stove, Gas Fireplace, Outdoor, Indoor



### FIREBRICK & MORTAR KIT

Kit includes 5 Firebox Bricks and 2 lbs Dry Mix 211. Our Firebox Bricks are perfect for intermediate duty for building new fireplaces or to replace old or broken bricks in existing fixtures (wood or coal stoves, furnaces, and fireplace inserts). They can also be used to line a fire pit in the backyard or anywhere else a brick is needed that can withstand high temperatures. Bricks measure 9" x 4-1/2" x 1-1/4".



**KT603211 5 bricks, 2 lbs. mortar per case**

USE: Outdoor, Indoor



**COMING SOON** *Contact customer service for details.*

**PERFECT PIZZA & BBQ GOURMET HICKORY HUNKS™ 11083**

**HEAT TRAPPER™ 10501**  
*Insulative, lightweight, castable refractory cement.*





## FIREBOX BRICKS

These firebricks can be used to build new fireplaces or to replace old or broken bricks in existing fixtures (wood or coal stoves, furnaces, and fireplace inserts). Color may vary. They can also be used to line a fire pit in the backyard or anywhere else a brick is needed. Meets or exceeds residential building codes regarding fireplace and chimney construction. Color may slightly vary. Not for direct food contact. Each brick measures 9" x 4.5" x 1.25".

- ☀️ **603-1**    **6 Bricks per case - Ivory**
- 10602**    **6 Bricks per case - Red**

USE: Outdoor, Indoor



## SOAP SPLIT FIRE BRICKS

Slender fire bricks half the size of typical fire bricks. Commonly used for decorative fireplace designs, such as herringbone or chevron designs, but can also be used to build or repair outdoor fire pits, pizza ovens and stove linings. Meets ASTM C-27 (Low Duty), C-1261 and the requirements of national & international building codes regarding fireplace and chimney construction. Color may slightly vary. Not for direct food contact. Each brick measures 9" x 2.25" x 1.25".

- 16035**    **12 Bricks per case - Ivory**
- 160250**    **12 Bricks per case - Red**

USE: Outdoor, Indoor



## SOAPSTONE FIRE BRICKS

Rutland's Soapstone Fire Bricks provide a **food-safe** surface and are best-in-class for the absorption and retention of heat. Incredibly dense, heavy fire bricks that will easily withstand temperatures produced by any wood fires, radiating heat much longer than clay fire bricks. Featured in high-end pizza ovens and masonry heaters, soapstone adds a natural and unique beauty along with improved performance. The ideal fire brick for pizza ovens, but works great for fireplaces, surrounds, and outdoor BBQ pits. Each brick measures 9" x 4.5" x 1.25".

- 16051**    **6 Bricks per case - Blue-gray**

Uses: Outdoor, Indoor, **Food-Safe Surface**





**TSP CLEAN & PREP®**

Heavy-duty indoor, outdoor cleaner & degreaser. Cleans and prepares surfaces for painting by allowing for superior adhesion. Great for woodwork, walls, decking, siding, and concrete & masonry. Helps fight mold & mildew, removes heavy deposits of grease & grime, smoke, soot stains, and chalked paint. Use to clean lead-contaminated dust from surfaces. Can be combined with bleach for an even stronger solution. Use phosphate-free product in areas where use of phosphate is strictly regulated. For heavy duty indoor cleaning, dissolve 2 scoops in 1 gallon of hot water.

**CLTSP01 Technical-grade Trisodium Phosphate**  
**16 oz. bag (15 per case)**

**CLTS01 Phosphate-free for heavier outdoor use**  
**16 oz. bag (15 per case)**

USE: Woodwork, Walls, Decking, Siding, Concrete & Masonry



**JUST GRATE®**

Grill grate and BBQ cleaner makes cleaning your grill easy. The powerful formula quickly gets rid of caked on food, carbon, grease, and baked on deposits that can ruin the taste of your favorite foods. Fresh citrus scent.

**462 16 oz bottle (6 per case)**

USE: Grill grates & BBQs

*WARNING: These products can expose you to harmful chemicals. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).*



**FIRE PREVENTION**

**FIRE BLANKET**

A tried-and-true solution to quickly, and easily extinguish small fires. Rutland's Fire Blanket is a woven fiberglass used to smother fires by depriving it of oxygen. The best solution for liquid or grease fires, but will work on ordinary combustible fires, like wood fires. Ensure proper fire safety and peace of mind by keeping one accessible in any cooking area, fire pit or fireplace, or vehicles. Unlike traditional fire spray extinguishers, fire blankets are easily stored and accessible, will never expire, and non-mechanical, so there's no potential of it breaking while it's stored away. Rutland's Fire Blanket is composed of strong woven fiberglass fabric, and features straps for quick and intuitive deployment. Each fire blanket measures 40" x 40".

- 10911 1-pack**
- 19112 2-pack**
- 19114 4-pack**





## MISC. NEW PRODUCTS

### LONG BURN LOGS™

Long Burning eco-friendly logs, convenient box of 6. Each log is 2.75 pounds and burns up to two hours. 100% premium recycle hardwoods with no paraffin wax. Burns longer, hotter, and cleaner. Burns 2-3 times longer than cord wood. **Two free JUMBO fire starters included in every box!**

**10216 Six 2.75 lb. logs (1 per case)**



USE: Fireplace, Wood Stove, Firepit



### 5-PIECE UNIVERSAL GAS APPLIANCE HOOK-UP KIT

Everything you need for easy installation of most gas appliances! Kit includes:

- 22" flexible whistle-free gas connector with 1/2" female flares
- Brass shutoff valve with 1/2" female pipe thread x 1/2" male flare
- 1/2" male flare x 1/2" male pipe
- 1/2" male flare x 3/8" male pipe
- 1/2" male flare x 3/8" female pipe
- Teflon tape

**GAK1 (12 per case)**

USE: Gas Appliances



### HOT DOG SNOW & ICE MELT

Our Ice Melt draws moisture from the air and ice while generating heat, which enables it to work when other deicers cannot at temperatures down to -25°F. This deicer is safe to use around pets, on concrete, and vegetation when used correctly. Covers up to 5000 sq. ft. Calcium Chloride formulated to be environmentally safe and easily spreadable. Concentrated formula guarantees long-term, maximum effectiveness from season to season. Non-corrosive & non-conductive.

**HD10 10 lb jug (2 per case)**

**HD10BG 10 lb bag (2 per case)**

USE: Driveways, Sidewalks, Porches, Patios



### SILICA SAND

Our Silica Sand is ideal for all gas burning fire pits and fire places (except Liquid Propane). This striking Natural Silica Sand Enhances the natural beauty of fire, while modernizing classic looks.

**15810 13 lb pail (2 per case)**

USE: Gas Burning Fire Pits & Fire Places



# ***FIREPLACE & HEARTH***





## FIRE STARTERS

### SAFE LITE® FIRE STARTER SQUARES

Easy to light - even when wet - and burn up to 10 minutes per square! Only 1 - 2 squares are needed to start a fire. Simply break off 1 - 2 squares and set them on wood or pellets. Light by touching a flame to the rough edge of a square. These environmentally friendly, non-toxic squares are made of compressed recycled wood chips, paper fiber, and wax. Will not flavor food.

- ☀️ **50B** Carton of 144 Squares (8 per case)
- ☀️ **50C** Carton of 24 Squares (24 per case)

USE: BBQ, Grills, Smokers



### ONE MATCH® FIRE STARTER GEL

A thick, odor-free, gelled fire starter for quickly and easily starting any fire! Will not flavor food.

- 48** 8 fl oz Bottle (12 per case)
- 49** 16 fl oz Bottle (12 per case)
- ☀️ **49Q** 32 fl oz Bottle (12 per case)

USE: BBQ, Grills, Smokers



## RAINBOW FLAME® CRYSTALS

### RAINBOW FLAME® CRYSTALS

A family favorite - enjoy beautiful blue and green flames! Simply shake 1/2 cup, or toss the whole stick, onto a bed of hot coals. Not for use in gas units or in fires that will be used to prepare food.

- ☀️ **715** 1 lb Canister (12 per case)
- 715C** 1.5 oz Short Toss-In Stick (36 per case)

USE: Fireplace, Fire Pit, Wood Stove, Outdoor, Indoor



**WARNING:** These products can expose you to harmful chemicals. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## CREOSOTE REMOVER CANISTERS (3-PACK)

Contains 3 canisters to prevent creosote build-up in chimneys. Safe to use in all chimneys and wood-burning appliances. Simply toss one canister onto a bed of hot coals to turn sticky, tar-like creosote into brushable ash and prevent further build-up from occurring. Canisters burn safely to ash. Use 1 or more canisters per week as needed. Will not damage catalytic converters.

### 97G Three 3 oz Canisters (12 per case)

USE: Fireplace, Wood Stove



## CREOSOTE REMOVER

Keeps creosote build-up at bay! Add 1-2 scoops to a fire once per week or more often as needed. Safe for use in all chimneys and wood-burning appliances. Will not damage catalytic converters.

-  97 1 lb Tub (12 per case)
-  98 2 lb Tub (6 per case)

USE: Fireplace, Wood Stove



## LIQUID CREOSOTE REMOVER

Great for all stove and flue types, but best for pellet stoves where granules fall through the burner pan. Spray on an existing fire or pre-treat fuel before adding to a fire to make a chimney safer and more efficient.

-  97L 32 fl oz Spray Bottle (6 per case)

USE: Fireplace, Wood Stove, Pellet Stove, Outdoor, Indoor







**IMPORTANT!** RECOMMENDED FREQUENCY OF SOOT/CREOSOTE REMOVER USE BASED ON WOOD TYPE BURNED



**SOFTWOODS**

- |            |            |
|------------|------------|
| Aspen      | Basswood   |
| Balsam Fir | Box Elder  |
| Cedar      | Cottonwood |
| Pine       | Hemlock    |
| Poplar     | Willow     |

**LOW BTU**

Burn at lower temperatures  
Tend to be more porous woods with oils and resins that coat fireplace or stove in soot/creosote

**RUTLAND Tip**  
Use soot/creosote remover 6-7 times per week



**SOFT HARDWOODS**

- |             |           |
|-------------|-----------|
| Birch       | Hackberry |
| Cherry      | Spruce    |
| Douglas Fir | Sycamore  |
| Elm         | Walnut    |
| Red Maple   | Yew       |

**MID BTU**

May contain some oils and resins that create some soot/creosote

**RUTLAND Tip**  
Use soot/creosote remover 2-3 times per week



**HARDWOODS**

- |             |              |
|-------------|--------------|
| Ash         | Apple        |
| Beech       | Dogwood      |
| Hickory     | Hawthorn     |
| Oak         | Mulberry     |
| Sugar Maple | Osage Orange |

**HIGH BTU**

Burn at higher temperatures  
Dry, dense woods that burn cleanly and create very little soot/creosote

**RUTLAND Tip**  
Use soot/creosote remover 1 time per week

Estimates based on assumption that wood is burned daily during burn season. Actual BTUs may vary depending on region and specific type of wood. The potential exists for creosote buildup regardless of the wood type used if the wood is burning below 200°F

## SOOT REMOVERS

### **KWIK-SHOT® SOOT STOPPER CANISTERS (3-PACK)**

Contains 3 canisters to control soot build-up in fireplaces, wood or coal stoves, furnaces, and boilers. Simply toss one canister onto a bed of hot coals to clean existing soot and prevent further deposits from forming. Canisters burn safely to ash. Use 1 or more canisters per week as needed.

**100G Three 3 oz Canisters (12 per case)**

USE: Fireplace, Wood Stove

---



### **SOOT SWEEP® SOOT DESTROYER®**

Controls soot build-up in fireplaces, wood or coal stoves, furnaces, and boilers. Add 1-2 scoops to a fire once per week or more often as needed.

**100 1 lb Tub (12 per case)**

 **100B 2 lb Tub (6 per case)**

USE: Fireplace, Wood Stove

---



### **LOG BRIGHT® GAS LOG SOOT REMOVER**

Spray on gas fireplace logs to safely remove and control future soot buildup, giving them a “like new” appearance. Easy to use, this spray-on cleaner does not require scrubbing or wiping off. Use on vented and vent-free liquid propane and natural gas units. Will not discolor ceramic logs or harm burners. Do not use on white birch or fiber logs.

**570-6 16 fl oz Spray Bottle (6 per case)**



USE: Gas Fireplace



### **BURN INDICATOR**

Monitors the performance of a wood- or coal-burning stove. See the potential for creosote build-up at a glance. Magnetically attaches to vertical, single-wall pipe or cooktop surface of a wood or coal stove. Indicates overheating or low-temperature creosote build-up hazard.

#### **701-6 1 Magnetic Burn Indicator (6 per case)**

USE: Wood Stove, Coal Stove, Indoor



### **STACK-N-STORE™ STEEL BRACKETS**

Set of four heavy-duty, powder-coated corner brackets for building storage racks, shelves, and worktops in almost any size. Build a wood box to keep firewood off the ground to improve drying and to keep it away from pests and decay, or using more than one set, create storage shelves. Just screw or nail these brackets to any length of 2" x 4" lumber and the possibilities are endless!



#### **30360R 4 Brackets Per Box (6 per case)**

### **FIREPLACE GLOVES**

Made from genuine cowhide leather and lined with cotton fabric. Gloves have a cuff that extends up the forearm for additional protection. Use for fireplaces, wood stoves, grills, and fire pits. These gloves are NOT rated fireproof or flame resistant. To prevent injury, avoid direct contact with open flames or smoldering embers. One size fits most. Red.



#### **702 1 Pair of Gloves**



# MAINTENANCE



**CLEANERS**



## **FIREPLACE & WOOD STOVE GLASS CLEANER**

Formulated to remove smoke, soot, and creosote residue from glass doors of fireplaces and wood stoves. Spray-on cleaner does not contain dangerous acids or ammonia. Just spray on and wipe off - it's that easy! In no time at all, fireplace or stove glass will have that "like-new" appearance for continued enjoyment of leisure fires.

 **82**    32 fl oz Spray Bottle (6 per case)



### **CLEAR GLASS STOVE, GRILL & HEARTH CONDITIONING GLASS CLEANER**

Non-scratching formula consisting of micro-scrubbers that remove baked-on soot, creosote, carbon, and other mineral residues from glass doors of fireplace inserts, and coal-, oil-, and wood-burning stoves and pellet stoves. Ammonia-free. Leaves behind a protective silicone layer to make future cleanings even easier!

☀️ **84** 8 fl oz Bottle (12 per case)



### **MULTI-SURFACE PRO CLEAN**

This versatile cleaner conditions, cleans, and protects a variety of surfaces. The ammonia-free formula is perfect for use on glass, thermal glass, stainless steel, chrome, aluminum, porcelain, tile, ceramic range top, oven doors, sealed stone, kerosene heater glass, and fiberglass shower doors. Clean citrus scent. NOT for use on cars, windows, plastic (ex. microwave oven doors), plexiglass, stainless look or chrome look finishes.

☀️ **185** 8 fl oz Bottle (12 per case)



### **WHITE-OFF® GLASS CLEANING CREAM**

Specially formulated for the removal of white residue on gas log fireplace glass doors. Non-abrasive and easy to use, this glass cleaning cream does not scratch or cause micropitting. Ammonia-free.

☀️ **565** 8 fl oz Bottle (12 per case)



### **BRICK & STONE CLEANER**

Removes stubborn creosote or soot build-up on bricks or stone surrounding a fireplace. Industrial strength solvent will penetrate and dissolve build-up on most any stone or sealed brick without use of dangerous acids. Can also be used on an asphalt roof to remove chimney smoke and grime.

☀️ **83-6** 16 fl oz Spray Bottle (6 per case)



**WARNING:** These products can expose you to harmful chemicals.  
For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



## CEMENTS & MORTARS

NAME	CURE TYPE	STICKS TO MASONRY/METAL	INDOOR/OUTDOOR USE	TEMP RATING (F)	APPLICATION LAYER*
FIREPLACE MORTAR (63, 63B, 63G)	HEAT CURE	MASONRY	INDOOR	2000°	1/8" - 1/4"
BLACK FURNACE CEMENT (64A, 64C, 64, 65)	HEAT CURE	BOTH	INDOOR	2000°	UP TO 1/8"
STOVE & GASKET CEMENT (77, 78)	AIR DRY	BOTH	INDOOR	2000°	UP TO 1/8"
FIBERGLASS GASKET CEMENT (77E, 78E)	AIR DRY	BOTH	INDOOR	2000°	UP TO 1/8"
CHIMNEY MASONRY PATCH (89)	AIR DRY	MASONRY	BOTH	200°	1/8" - 1/2"
DRY MIX 211 (211)	AIR DRY	MASONRY	BOTH	2550°	1/16" - 1"
CASTABLE REFRACTORY CEMENT (600, 601)	AIR DRY	MASONRY	BOTH	2200°	1/2" - 9"
REFRACTORY CEMENT (610, 611)	HEAT CURE	MASONRY	INDOOR	2000°	UP TO 1/4"
STOVO (615)	HEAT CURE	BOTH	INDOOR	2000°	1/8" - 1/4"
PIPE INSULATING CEMENT (623)	AIR DRY	BOTH	INDOOR	300°	1/2" +

**HEAT CURE:** Allow to air-dry for 24 hours. Burn a low ~250°F fire for about 2 hours, then build the fire up to ~500°F for an additional hour. Learn more about heat curing and watch demonstrations:



Scan to view our Cements & Mortars Minute Clinic.





**E-Z SPREAD FIBERGLASS STOVE GASKET CEMENT**

Designed to be the easiest gasket cement for affixing fiberglass gaskets to steel and cast iron. Very easy to spread and control application and will not expand or contract during continued use. Apply in beads of 1/8" or less. 2000°F temperature rating. New and improved, no longer requires heat cure. Black.

- ☀️ **77E** 2.3 fl oz Tube (12 per case)
- ☀️ **78E** 10.3 fl oz Cartridge (12 per case)



USE: Fireplace, Wood Stove, Indoor



**STOVE & GASKET CEMENT - THE ORIGINAL**

This cement pulls double duty because not only can this cement adhere any fiberglass gasket to most any metal, it can also be used to fix those small cracks, pinholes, and leaks in a cast iron stove. Available in a handy squeeze tube or in a larger caulk gun-ready size, this cement will help restore a stove to safe and efficient operation. Apply in beads of 1/8" or less. 2000°F temperature rating. Black.

- ☀️ **77** 2.3 fl oz Tube (12 per case)
- ☀️ **78** 10.3 fl oz Cartridge (12 per case)



USE: Fireplace, Wood Stove, Indoor



**REFRACTORY CEMENT**

An ideal high-heat cement for masonry joints 1/4" or less. Pre-mixed, easy to trowel, and fiber reinforced, this cement can be used to set, bond, and repair cracked or broken firebricks in stoves, fireplaces, and furnaces as well as for building fireplace boxes. Its thick, smooth consistency makes this cement perfect for use as mortar between firebricks. Meets ASTM E136-04. 2000°F temperature rating. Requires heat cure. Buff.

- ☀️ **610** 64 fl oz Tub (6 per case)
- ☀️ **611** 128 fl oz Pail (2 per case)

Heat Cure Required



USE: Fireplace, Wood Stove, Indoor



**WARNING:** These products can expose you to harmful chemicals. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



**CASTABLE REFRACTORY CEMENT**

An exceptionally strong dry-mix cement that chemically sets and dries as hard as brick. Just add water! Perfect for casting into custom designs because it holds its shape while drying. Can even be used as the sole material when casting a solid stove bed or outdoor oven. 2200°F temperature rating. Does not require heat cure! Cast up to 9" depth. Color may vary.

- 600 12.5 lb Pail (2 per case)**
- 601 25 lb Pail (1 per case)**



USE: Fireplace, Wood Stove, Pellet Stove, Outdoor, Indoor



**FURNACE CEMENT**

Premixed and ready to use, this is one of the easiest cements to apply. Use this smooth consistency cement to bond and seal metal to metal or metal to masonry joints less than 1/8". Repair a crack, seal the collar to the top of a wood stove, or seal between firebricks and prefabricated fireplace. Use anywhere a quality high-temperature adhesive is required for furnaces, firebrick repair, filling gaps, sealing joints, or gluing ceramic logs. Adheres to metal, stone, and firebricks, creating a permanent smoke- and gas-tight seal. 2000°F temperature rating. Heat cure required.




- 64A 8 fl oz Tub (12 per case)**
- 64C 10.3 fl oz Cartridge (12 per case)**
- 64 16 fl oz Tub (12 per case)**
- 65 32 fl oz Tub (6 per case)**

USE: Fireplace, Wood Stove, Indoor



**STOVO® STOVE MORTAR**

Ready-to-use, premixed, and general-purpose for repairing or relining firebrick in interior stoves, furnaces, boilers, incinerators, Franklin stoves, barbecues, and fireplaces. Adheres to metal or masonry and will prevent air and gas leaks around flue and chimney joints, ash pit doors, and small cracks between bricks and linings. Apply in layers 1/4" or less and allow to air dry for 24 hours between layers. 2000°F temperature rating. Requires heat cure. Buff.



- 615 32 oz Tub (6 per case)**






USE: Fireplace, Wood Stove, Indoor





**FIREPLACE MORTAR**

Perfect for repairing small chips or cracked firebrick, re-pointing mortar joints between firebricks, and bonding firebricks together. Adheres masonry to masonry for brick, firebrick, and stone. Use for cracks 1/8" deep or less. If deeper, apply multiple layers of -1/8" and allow 24 hours to dry between layers. Easy to apply with a caulking gun and will last for years. Sets as hard and as strong as firebrick after curing and can withstand the high temperatures produced by a wood fire. 2000°F temperature rating. Requires heat cure.

-  **63 Black 10.3 fl oz Cartridge (12 per case)**
-  **63B Buff 10.3 fl oz Cartridge (12 per case)**
-  **63G Gray 10.3 fl oz Cartridge (12 per case)**

 Heat Cure Required



USE: Fireplace, Wood Stove, Indoor

**DRY MIX 211®**

A refractory mortar ideal for joining or repairing masonry flue tile in any gas or wood fireplace and wood, coal, or pellet stove chimney. Just add water, mix, and trowel on to seal and join flue tiles. It can also be used as a parge coating (thin over-coat) when building fireboxes to give a fireplace a nice, even, dark gray finish. Meets NFPA 211 Standards and NYSCMA Tek 4.0 Specifications. 2550°F temperature rating. Does not require (but is stronger with) heat cure. If applying in layers, do not exceed 1" per layer and allow 24 hours to dry between layers. Dark Gray.

-  **211 10 lb Pail (4 per case)**



USE: Fireplace, Wood Stove, Pellet Stove, Gas Fireplace, Outdoor, Indoor



**FIREBOX BRICKS**

These firebricks can be used to build new fireplaces or to replace old or broken bricks in existing fixtures (wood or coal stoves, furnaces, and fireplace inserts). Color may vary. They can also be used to line a fire pit in the backyard or anywhere else a brick is needed that can withstand high temperatures up to 2700°F. Each brick measures 9" x 4.5" x 1.25".

- 604-1 Buff 6 Bricks per case**



USE: Outdoor, Indoor



**WARNING:** These products can expose you to harmful chemicals. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).





**FIBERGLASS INSULATION**

An insulation strip with a peel-off, self-adhesive backing that is ideal for forming a smoke- and gas-tight seal between a fireplace insert and existing masonry. For the best performance, replace insulation every time the insert is removed for cleaning. Rated to 250°F.

105 10' Roll (6 per case)



## GRAPHO-GLAS® STOVE GASKETS

Graphite impregnated, braided fiberglass gasketing engineered to provide superior sealing, protection, and longevity. Also resist abrasion, creosote and soot adhesion, and temperatures up to 1000°F. Used by major stove manufacturers and to replace worn-out gaskets in wood and coal stoves or fireplace inserts. Annual replacement of stove gaskets ensures a tight seal for maximum airtight operation and efficiency.

### KITS (Includes Gasket & Fiberglass Stove Gasket Cement) (6 per case)

☀️ 95A-6	7' x 5/16"	Rope
☀️ 95-6	7' x 5/8" x 3/16"	Flat
☀️ 95W-6	7' x 3/4" x 1/4"	Flat
☀️ 96-6	7' x 3/8"	Rope
☀️ 96N-6	7' x 1/2"	Rope
☀️ 96W-6	7' x 5/8"	Rope
☀️ 99-6	7' x 3/4"	Rope
☀️ 99N-6	7' x 7/8"	Rope



Also available by the foot upon request.  
Call 800-544-1307 for pricing.



### BAGGED (Cement not included)

90	7' x 5/8" x 3/16"	Flat	92W	7' x 3/4"	Rope
91	7' x 3/8"	Rope	94N	5'4" x 7/8"	Rope
91N	7' x 1/4" - 5/16"	Rope	94	6' x 1"	Rope
92	5' x 1/2" - 5/8"	Rope			

### SPOOLS

720	157' x 5/8" x 3/16"	Flat	724	65' x 5/8"	Rope
721	200' x 5/16"	Rope	725	47' x 3/4"	Rope
721N	200' x 1/4"	Rope	725W	40' x 7/8"	Rope
722	132' x 3/8"	Rope	726	25' x 1"	Rope
723	88' x 1/2"	Rope	516GG	75' x 5/16"	Griddle Gasket
723W	100' x 7/16"	Rope			



### WHITE FIBERGLASS GASKETS SPOOLS

721P	200' x 5/16"	Rope
726P*	25' x 1"	Rope
78LA*	25' x 7/8"	Lopi Rope

\*Special Order, Please Call

### GASKET SPOOL DISPLAY

Holds 5-6 gasket spools with convenient measuring tape. Black.

108E 24" x 12"



### STOVE WINDOW GASKETS

Designed to securely seal stove window glass in stove doors and openings. Peel off protective paper and wrap self-adhesive tape over the glass edge. No additional cement is needed. Available in Black with graphite or White.

93	Black	4'6" x 11/16"	Bagged (12 per case)
727	Black	80' x 11/16"	Spoiled (1 per case)
727P	White	80' x 13/16"	Spoiled (1 per case)
729	Black	90' x 13/16"	Spoiled (1 per case)



Scan to view our video illustrating how to replace a stove door gasket.



**WARNING:** These products can expose you to harmful chemicals. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).









**WATER GLASS CEMENT FLOOR SEALER**

This unique formula is a multi-use sealant and adhesive. When diluted, it becomes an excellent stain-resistant concrete sealant against oils while simultaneously preventing concrete dust. Use full-strength for an effective and inexpensive adhesive for sealing gaskets, cartons, and applying labels.

146 1 gal Jug (4 per case)

USE: Indoor



PAINTS



**HI-TEMP PAINTS**

Provide both a beautiful flat black finish as well as durability to any stove or grill, and will look great for years while keeping rust at bay. Use outdoors or indoors. Adhere to steel, cast iron, aluminum, and brick, and are great for grills, stoves, smokers, stove pipes, fireplace inserts, furnaces, barbecues, mailboxes, lampposts, fireplace tools, brass, firebrick, and chimney caps. Flat Black.

**PREMIUM 1400°F BRUSH-ON PAINT WITH LOW VOC**

☀️ 81V 16 fl oz Can (6 per case)

**1200°F HI-TEMP PAINTS**

☀️ 80 12 fl oz Spray Can (12 per case)

☀️ 81 16 fl oz Can\* (6 per case)

*\*Product 81 not for sale in California*

USE: Outdoor, Indoor



**WARNING:** These products can expose you to harmful chemicals. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



**STOVE POLISH** *not for sale in California*

Transforms old, dull, cast iron stoves into like-new appearance! Combines three different waxes with some of the blackest pigments to renew and protect cast iron. Non-toxic and non-flammable, this polish can be buffed to a deep lustrous glow, leaving cast iron looking better than new. Prevents deterioration to the exteriors of stoves, grills, ornamental ironwork, and heating accessories even during extended storage. Not for use on painted, powder-coated, stainless, raw, or sandblasted steel. Black.

**70 2.3 fl oz Tube (12 per case)**



USE: Outdoor, Indoor



**LIQUID STOVE & GRILL POLISH** *not for sale in California*

Protects cast iron and steel heating and cooking appliances from getting dull and rusty. Apply polish and buff to a high luster to restore that like-new appearance. Safe to use – non-flammable and non-toxic. One bottle should lightly polish an average sized, free-standing wood stove or a large grill. Not for use on painted, powder-coated, sand-blasted, stainless, or raw steel surfaces. Black.

 **72 8 fl oz Bottle (12 per case)**



USE: Outdoor, Indoor



**WILLIAM'S® STOVE POLISH** *not for sale in California*

Brings a low-luster, dark gray finish to any unpainted cast iron appliances. Easy to apply. Buff after drying. Can also be used on wood and coal stoves, barbecues, hibachis, iron pots, iron kettles, and grills. Not for use on painted, powder-coated, sand-blasted, stainless, or raw steel surfaces. Dark Gray.

**WI-00710 2.3 fl oz Tube (12 per case)**



USE: Outdoor, Indoor





**SEAL IT RIGHT® FLEXIBLE LATEX SEALANT** *not for sale in California*

A non-permanent seal that expands and contracts with heat variations. For use with metal and aluminum. Use to install and maintain direct vent appliances, gas-burning systems, pellet stoves, and metal flues on wood and coal stoves. Easily removed for cleaning and inspection. Not an adhesive. 800°F continuous temperature rating. Black. Does not require a heat cure.

- ☀️ **641C** 2.3 fl oz Tube (12 per case)
- ☀️ **641** 10.3 fl oz Cartridge (12 per case)



USE: Fireplace, Wood Stove, Pellet Stove, Gas Fireplace, Indoor, Outdoor



**HIGH HEAT SILICONE SEALANT**

A great solution for sealant needs – seals off gases and smoke permanently, with limitless uses in the home or on job sites. Use to seal fireplace inserts, repair solar panels, or seal a chimney cap to withstand wind, rain, and hot smoke. Available in 600°F RTV and 500°F RTV temperature ratings and two colors (Red and Black) as well as Clear. Does not require a heat cure.

**600°F RTV**

600°F RTV temperature rating and available in Red and Black.

- ☀️ **76R** Red 10.3 fl oz Cartridge (12 per case)
- ☀️ **76B** Black 10.3 fl oz Cartridge (12 per case)



USE: Fireplace, Wood Stove, Pellet Stove, Gas Fireplace, Indoor, Outdoor



**500°F RTV**

500°F RTV temperature rating and available in Black and Clear. Choose from a handy 2.7 fl oz tube for small repairs or a 10.3 fl oz caulk gun cartridge for larger jobs.

- ☀️ **76** Black 10.3 fl oz Cartridge (12 per case)
- ☀️ **76A** Black 2.7 fl oz Tube (12 per case)
- ☀️ **76C\*** Clear 10.3 fl oz Cartridge (12 per case)
- 76CT\*** Clear 2.7 fl oz Tube (12 per case)



\*Food safe, FDA regulation #21 CFR 177.2600.





# **BRUSHES & RODS**





## CHIMNEY SWEEP® WIRE CHIMNEY BRUSHES

Designed with the homeowner in mind, these brushes have an open, single spiral construction with 6" of fill, plated shafts, and 1/4" NPT threading for easy coupling with fiberglass rods or pull rings. Oil-tempered spring wire. Use in masonry and metal liners. Use in cool chimney only. Use with RUTLAND® Rods 10624, 10672, and KRK-18 on page 24.



**Tip:** Be sure to match the fitting of brushes and rods (NPT - NPT or 1/4-20 - 1/4-20). Use a **Rutland Reducer** to allow the use of mismatched brushes and rods!

### ROUND WIRE

- 16406 6" Round (4 per case)
- 16407 7" Round (4 per case)
- 16408 8" Round (4 per case)
- 16409 9" Round (1 per case)
- 16410 10" Round (1 per case)

### SQUARE WIRE

- 16506 6" Square (4 per case)
- 16507 7" Square (4 per case)
- 16508 8" Square (4 per case)
- 16510 10" Square (1 per case)
- 16511 11" Square (1 per case)
- 16512 12" Square (1 per case)



### RECTANGULAR WIRE

- 36531 6" x 10" Rectangular (1 per case)
- 16532 7" x 11" Rectangular (1 per case)
- 16533 8" x 12" Rectangular (1 per case)

## CHIMNEY SWEEP® ROUND POLY CHIMNEY BRUSHES

Specially designed for stainless steel, liners, and stove pipes. These sturdy poly brushes have 6" of fill and are acid resistant. Fittings are 1/4" NPT threading. Use in masonry and metal liners. Use in cool chimney only. Use with RUTLAND® Rods 10624, 10672, and KRK-18 on page 24.



- ☀️ 16906 6" Round Poly (4 per case)
- ☀️ 16908 8" Round Poly (4 per case)

## CHIMNEY SWEEP® PELLET STOVE & DRYER VENT BRUSHES

Designed to clean both pellet stove vents and dryer vents. Brushes can easily navigate a sharp turning radius without getting caught in elbows. Brush filament is 0.020" poly. For light cleaning only. For heavier buildups, use RUTLAND® Pellet Stove Brushes PS-3, PS-4, or PS-5, shown below.

- 17409 3" Brush with 10' Flexible Handle (4 per case)
- 17410 4" Brush with 10' Flexible Handle (4 per case)
- 17419 3" Brush with 20' Flexible Handle (4 per case)
- 17420 4" Brush with 20' Flexible Handle (4 per case)



## CHIMNEY SWEEP® PELLET STOVE BRUSHES

Made with poly bristles and available in 3", 4", and 5" round sizes. Heavy-duty ball tip guides brushes through narrow offsets and bends. Designed for heavy cleaning. Fittings are 1/4-20 thread. Use with RUTLAND® Rods 25P-5 and PSR-20 on page 24.

- ☀️ PS-3 3" Round Poly (4 per case)
- ☀️ PS-4 4" Round Poly (4 per case)
- PS-5 5" Round Poly (1 per case)





**FIBERGLASS CHIMNEY BRUSH EXTENSION RODS**

Designed with the DIY homeowner in mind. Rods are available individually in lengths of 4' and 6' and use 1/4" NPT threading to connect to a chimney brush. Attach to a RUTLAND® Chimney Sweep® Wire or Poly Brush to clean a chimney from the top down or up through the open fireplace. The fiberglass is flexible enough to handle slight offsets, but not enough to bend around sharp corners. Cleaning in an up-and-down motion with these rods will provide the power necessary for a satisfactory result.



- ☀️ **10624**    4'    Individual Rod    Bends <90° (24 per case)
- ☀️ **10672**    6'    Individual Rod    Bends 90° (24 per case)
- ☀️ **KRK-18**    18'    Kit (Six 3' Rods)    Bends 45° (5 per case)

**FLEXIBLE POLY PELLET STOVE RODS**

Poly rods designed to easily maneuver through 30° and 45° offsets, 0.250" diameter and 1/4-20 thread. Use with RUTLAND® Chimney Sweep® Pellet Stove Brushes.



- ☀️ **25P-5**    5'    Individual Rod    Bends 360° (10 per case)
- ☀️ **PSR-20**    20'    Kit (Eight 2.5' Rods)    Bends 360° (5 per case)

**PULL RING - HOMEOWNER**

Designed for the DIY homeowner to attach to RUTLAND® Extension Rods to provide an attachment point for ropes to pull RUTLAND® Chimney Sweep® Cleaning Brushes through a chimney during cleaning. Available with 1/4" NPT threading.

- 16202**    1/4" NPT (12 per case)
- W38PTL**    3/8" NPT (12 per case)



**REDUCER**

Allows use of mismatched brushes and rods. Female connectors on both sides will adapt a brush and rod set to match each other. Product 1438 converts 1/4" NPT to 3/8" NPT, and 1439 converts 1/4" NPT to 1/4-20 threading.

- 1438**    1/4" to 3/8" NPT (12 per case)
- 1439**    1/4" NPT to 1/4-20 Threading (5 per case)







# PRODUCT INDEX

PRODUCT #	PAGE #	PRODUCT #	PAGE #	PRODUCT #	PAGE #
98P	5	30360R	17	78LA	25
98P03	5	702	17	108E	25
98P05	5	82	18	93	25
98A	5	84	19	727	25
97C5	5	185	19	727P	25
97C20	5	565	19	729	25
19701	5	83-6	19	146	27
19702	5	77E	21	81V	27
FN05	5	78E	21	80	27
49USA	6	77	21	81	27
50J	6	78	21	70	28
50W	6	610	21	72	28
715P	6	611	21	WI-00710	28
71599	6	600	22	641C	29
99N12	7	601	22	641	29
99N12G	7	64A	22	76R	29
99N217	7	64C	22	76B	29
99N217G	7	64	22	76	29
21125	8	65	22	76A	29
KT603211	8	615	22	76C	29
11083	8	63	23	76CT	29
10501	8	63B	23	16406	31
603-1	9	63G	23	16407	31
10602	9	211	23	16408	31
16035	9	604-1	23	16409	31
160250	9	105	24	16410	31
16051	9	95A-6	25	16506	31
CLTSP01	10	95-6	25	16507	31
CLTS01	10	95W-6	25	16508	31
462	10	96-6	25	16510	31
10911	10	96N-6	25	16511	31
19112	10	96W-6	25	16512	31
19114	10	99-6	25	36531	31
10216	11	99N-6	25	16532	31
GAK1	11	90	25	16533	31
HD10	11	91	25	16906	31
HD10BG	11	91N	25	16908	31
15810	11	92	25	17409	31
50B	13	92W	25	17410	31
50C	13	94N	25	17419	31
48	13	94	25	17420	31
49	13	720	25	PS-3	31
49Q	13	721	25	PS-4	31
715	13	721N	25	PS-5	31
715C	13	722	25	10624	32
97G	14	723	25	10672	32
97	14	723W	25	KRK-18	32
98	14	724	25	25P-5	32
97L	14	725	25	PSR-20	32
100G	16	725W	25	16202	32
100	16	726	25	W38PTL	32
100B	16	516GG	25	1438	32
570-6	16	721P	25	1439	32
701-6	17	726P	25		







**duravent**<sup>™</sup>  
GROUP

**RUTLAND**  
TRUSTED SINCE 1883

**CONTACT DURAVENT CUSTOMER SERVICE**  
*TO SPEAK WITH ONE OF OUR EXPERIENCED PROFESSIONALS!*

800.252.8467 . [retail@duraventgroup.com](mailto:retail@duraventgroup.com) . [duraventretail.com](http://duraventretail.com)

10/2024

